Assembly instructions – model X5

emagra ®
seating

Emagra office design

Used parts
(Note: Some parts may be different than images)

1. Gaslift	2. Casters	3. Armrests
4. Synchro mechanism	5. Seat	
6. Base	7. Backrest	8. Headrest
9. Screws		

Model X5 / armrests 1B, 3B

A	M6x30	10pcs	6 pcs armrests + 4 pcs mechanism
B	M8x14(15)	3pcs	Backrest
C	M5x14 (17)	1pcs	Headrest
		1 pcs	IMBUS

STEP 1
1. Insert armrests to the seat
2. Be aware of the correct position of the left and right armrests
3. Fasten the screws Ax6pcs

STEP 2
1. Fasten mechanism to the seat
2. Tighten the screws A x 4pcs

STEP 3:
1. Fasten backrest to the mechanism
2. Tighten the screws B x 3pcs

STEP 4:
1. Insert 5pcs of casters into the base, then insert gaslift into the opening in the base
2. Insert the gaslift into the corresponding hole in the mechanism

STEP 5:
1. Fasten headrest to the backrest
2. Tighten the screws D x 1pcs

User guide
Maintenance and attention
1. The chair can only be used by one person at a time.
2. Do not use the chair as a stool or ladder.
3. Do not use the chair unless all parts are properly assembled.
4. Do not use the chair untill all screws are properly tightened.
5. If the chair is damaged by external influences, do not use it without expert repair.
6. This is a mechanical product subjects to user stress, it is necessary to check the chair regularly and possibly tighten the screws.
For professional servis, please contact us by phone +420 463 034 155 or by mail export1@emagra.cz

5 let záruka
GUARANTY

Using instructions - model X5

emagra seating ®

Emagra office design

5 let záruka GUARANTY

Headrest adjustable in height and angle

Height regulation of backrest UP-DOWN

Separately adjustable lumbar support – height 10 cm, width 2,5 cm

Standard separately height adjustable (10 cm) lumbar support

Handle for heigth regulation of **F mechanism**

Control for synchro **mechanism F**

Handle for height regulation of **X mechanism**

Control for synchro **mechanism X**

Height regulation by gaslift

Armrests 1B – with softened polyurethane foam on the touch part: Height adjustable rotatable left/right

Screw for manual pressure control according users weight by tightening or loosening screw

4D adjustable **3B armrests** with softened polyurethane foam on the touch part
Options of regulation:
height and width
forward / backward
rotatable left/right

Handle for regulation of mechanics stiffness according to user weight

www.emagra.cz